BUYERSGUIDE

Mid-Size/Mid-**Price Digital** Consoles

By GeorgePetersen

ffordable mixing is here! Ideal for install or portable applications, here's a snapshot look at some medium-sized digital consoles capable of 24 or more channels — some a lot more — while having a fairly compact footprint that's less than 42 inches wide. All are less than 60 pounds, making these highly portable and prices of these units all fall under \$10K (some way under \$10K) and can vary somewhat — depending on options and selected system package configurations so check before shopping.



Input Channels/Local Pre's: 48/32 Max Sampling Rate: 96 kHz Faders: 33 **Onboard I/O:** 32/16 Remote I/O: GX4816, DX012, DX168, DT168, DX164W, DT164W Other Frame Sizes: SQ-5, SQ-6 Network Interfacing: d-Snake; Dante option Footprint/Weight: 31.7 x 20.3"; 23 pounds Notes: 32x32 USB interfacing; Dante/Waves option

allen-heath.com

Crest Audio Tactus

Input Channels/Local Pre's: 64/8

Max Sampling Rate: 96 kHz

Faders: 18 moving faders

.....

. . . .

cards

Ashly DigiMIX24



Input Channels/Local Pre's: 24/16 Max Sampling Rate: 48 kHz Faders: 1, assignable Onboard I/O: 24 analog; 2 USB Remote I/O: Dante option **Other Frame Sizes:** DigiMIX18 Network Interfacing: Dante option **Footprint/Weight:** 20 x 24"; 18 pounds Notes: 7" touch screen control; USB multi-track recording/playback option

ashlv.cor

Input Channels/Local Pre's: 40/24


Max Sampling Rate: 96 kHz

Faders: 21 faders

DiGiCo S21



Input Channels/Local Pre's: 56/16 Max Sampling Rate: 96 kHz Faders: 17 faders Onboard I/O: 16 XLR in; 3 XLR out Remote I/O: CDC I/O 3216 Other Frame Sizes: CDC-six, CDC eight-16, CDC eiaht-32 Network Interfacing: MADI optional Footprint/Weight: 19 x 22.5"; 33 pounds Notes: TabMix app for iPad control



midasconsoles.com



Max Sampling Rate: 48 kHz Faders: Virtual on touch screen **Remote I/O:** No stageboxes offered Mix Control App



Max Sampling Rate: 96 kHz ware controllers also offered Onboard I/O: SoundGrid I/Os. Other Frame Sizes: Numerous







Faders: 17

QSC TouchMix-30 PRO



Onboard I/O: 24 XLR in, 6 TRS ins; 18 TRS bus outs Other Frame Sizes: TouchMix-16 PRO Network Interfacing: USB, Ethernet routing to Touch-

Footprint/Weight: 18 x 17"; 17.5 pounds **Notes:** Direct multi-track capture/playback

gsc.com

Waves Audio eMotion LV1



Input Channels: 16 to 64 mono/stereo inputs Faders: Virtual via touch screen; Platform series hard-Remote I/O: SoundStudio STG-1608 stagebox Footprint/Weight: Varies by configuration Notes: Waves Audio eMotion LV1 Total Live System

offers complete turnkey mixing package

