

| Company                               | Model                          | Power                              | Analog Inputs                                                                                      | Digital Inputs                                                                                           | Output Connects                                  |  |
|---------------------------------------|--------------------------------|------------------------------------|----------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|--------------------------------------------------|--|
| Ashly Audio, Inc.                     | PE 3800                        | 1900                               | TRS/XLR Combo                                                                                      | AES                                                                                                      | Speakon                                          |  |
| BOSCH Security Systems Inc.           | DYNACORD H-5000                | 2 x 2500W                          | 2 XLR in/out, 2 Euroblock                                                                          | XLR (AES/EBU) with RCM 26                                                                                | NL4 , binding posts                              |  |
|                                       | DYNACORD H 2500                | 2 x 1450W                          |                                                                                                    |                                                                                                          |                                                  |  |
|                                       | Electro-Voice TG-7             | 2 x 2500W                          |                                                                                                    |                                                                                                          |                                                  |  |
|                                       | Electro-Voice TG-5             | 2 x 1450W                          |                                                                                                    |                                                                                                          |                                                  |  |
| Carvin                                | DCM3800L                       | 1150W                              | XLR & 1/4" TRS                                                                                     | NA                                                                                                       | Speakon NL4, binding posts                       |  |
| Crest Audio                           | Pro 9200                       | 2 x 2200W                          | Balanced male and femal XLR inputs with switch-configurable XLR polarity and sensitivity selection | n/a                                                                                                      | Speakon and five-way binding post                |  |
|                                       | CC 5500                        | 2 x 1800W                          | Combi XLR & 6.3mm inputs                                                                           |                                                                                                          | Speakon and 5-way binding post                   |  |
| Crown International                   | I-Tech HD (12000 HD)           | 4,500W                             | 2                                                                                                  | 2 (AES and Cobranet)                                                                                     | Two Speakon NL4, binding posts                   |  |
|                                       | Crown Macro Tech I (MA-12000i) |                                    |                                                                                                    | 0                                                                                                        | 50A Neutrik Speakon NL4MLP, binding posts        |  |
| Lab.gruppen                           | FP14000                        | 2 x 4400W                          | 2-channel (input + link)                                                                           | n/a                                                                                                      | Binding posts                                    |  |
|                                       | FP9000                         | 2 x 3000W                          |                                                                                                    |                                                                                                          |                                                  |  |
|                                       | FP7000                         | 2 x 2800W                          |                                                                                                    |                                                                                                          | Speakon/Binding posts                            |  |
|                                       | FP4000                         | 2 x 1600W                          |                                                                                                    |                                                                                                          |                                                  |  |
|                                       | FP10000Q                       | 4 x 2100W                          |                                                                                                    |                                                                                                          |                                                  |  |
|                                       | FP60000Q                       | 4 x 1250W                          |                                                                                                    |                                                                                                          |                                                  |  |
|                                       | PLM10000Q                      | 4 x 2300W                          |                                                                                                    | 2-channel Dante & AES/ EBU (input + link)                                                                |                                                  |  |
|                                       | PLM14000Q                      | 2 x 4350W                          |                                                                                                    |                                                                                                          |                                                  |  |
| Peavey                                | CS 4080 HZ                     | 2 x 2040W                          | Combi                                                                                              | n/a                                                                                                      | Speakon/Binding post                             |  |
|                                       | IPR 1600 DSP                   | 2 x 530W                           | 2 x Combi XLR or 1/4"; 2 x 1/4" patch                                                              |                                                                                                          | 2 Combi Speakon style or 1/4"                    |  |
| Powersoft                             | DIGAM K10                      | 2 x 4000W                          | 2 x balanced Neutrik Combo XLR                                                                     | AWS3                                                                                                     | Speakon NL4MD                                    |  |
| QSC Audio Products, LLC               | PLX3602                        | 3600W                              | 3-pin XLR & 1/4" TRS balanced                                                                      | N/A                                                                                                      | Neutrik NL4 Speakon and touchproof binding posts |  |
| Yamaha Commercial Audio Systems, Inc. | Yamaha PC9501, PC6501          | PC9501 1600W; PC6501 1100W         | XLR and Euroblock                                                                                  | N/A                                                                                                      | NL4 and 5-way binding posts                      |  |
|                                       | Yamaha TXn 6, 5, 4             | TX6n 3000W; TX5n 2200W; TX4n 1900W | XLR                                                                                                | MY-Card slot,( AES Standard), EtherSound, CobraNet, ADAT, MADI, A-Net, Rock-Net, Optocore, SDI Available | NL4, and 5 way binding posts                     |  |
|                                       | Yamaha P7000S                  | 1100W                              | 1/4" phono and XLR                                                                                 | N/A                                                                                                      | NL4 and 1/4"                                     |  |
|                                       | NEXO NX 4x4                    | 3300W                              | XLR                                                                                                | EtherSound optional                                                                                      | NL4 and 1/4"                                     |  |

|  | Power Draw                                  | Input Power                       | Size                                                                                                                 | Channels                         | DSP Description                                                                                                                                                                                                                                                                                                             | MSRP                                                                                                                            |
|--|---------------------------------------------|-----------------------------------|----------------------------------------------------------------------------------------------------------------------|----------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|---------------------------------------------------------------------------------------------------------------------------------|
|  | 22.6A @ 120VAC                              | Fixed 120 Or 230VAC               | 2RU 24 lbs                                                                                                           | 2                                | DSP input option available                                                                                                                                                                                                                                                                                                  | \$3,325                                                                                                                         |
|  | 12A @ 120V                                  | 100V - 240V, 50 - 60 HZ           | 2U/32 Lbs                                                                                                            | 2                                | RCM 26<br>IRIS-NET Control<br>FIR DRIVE                                                                                                                                                                                                                                                                                     | \$5,880 with RCM 26                                                                                                             |
|  | 8.3A @ 120VAC                               |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | \$5180 incl RCM 26                                                                                                              |
|  | 12A @ 120VAC                                |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | \$5,880 (incl. RCM26)                                                                                                           |
|  | 8.3A @ 120VAC                               |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | \$5,180 (incl. RCM26)                                                                                                           |
|  | 4.3A @ 120VAC                               |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | 90-250VAC 50-60Hz                                                                                                               |
|  | 2200W                                       | 90 to 132 VAC                     | 3.5" x 19" x 12.25" + 1.5" (2RU);<br>24 lbs.                                                                         | 2                                | N/A                                                                                                                                                                                                                                                                                                                         | \$3,290                                                                                                                         |
|  | 1740W                                       |                                   | 88.9mm x 482.6mm x 377.8mm<br>+ 31.8mm (2RU); 47 lbs.                                                                |                                  |                                                                                                                                                                                                                                                                                                                             | TBA                                                                                                                             |
|  | 14.6                                        | 100 - 265 VAC                     | 19"W x 3.5" H x 16.2" D; 28 lbs                                                                                      | 2                                | A new user-inspired DSP engine<br>co-developed with BSS Audio called<br>OMNIDRIVEHD. The new processing<br>engine features Linear Phase FIR filters.                                                                                                                                                                        | \$8,510                                                                                                                         |
|  |                                             | 100 - 240VAC                      |                                                                                                                      |                                  | None                                                                                                                                                                                                                                                                                                                        | \$6,855                                                                                                                         |
|  |                                             |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             |                                                                                                                                 |
|  | 23.9A @120 AC<br>12.5A @230V                | 130-265 V /65-135 V               | W: 483 mm (19"),<br>H: 88 mm (2 U),<br>Overall D: 396 mm (15.6"),<br>Mounting D: 358 mm (14.1")<br>12 kg (26.4 lbs.) | 2                                | Per channel selectable Voltage Peak<br>Limiter (VPL), Current Peak Limiter<br>(CPL), Very High Frequency (VHF),<br>Power Average Limiter (PAL), Adjust-<br>able Gain, Nomadlink Network, A+B<br>Output Bridge Mode                                                                                                          | \$6,645                                                                                                                         |
|  | 18.5A @120 AC<br>9.7A @230V                 |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | \$6,395                                                                                                                         |
|  | 16.8A @120 AC<br>8.7A @230V                 |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | \$5,295                                                                                                                         |
|  | 10.7A @120 AC<br>5.6A @230V                 |                                   |                                                                                                                      | 4                                |                                                                                                                                                                                                                                                                                                                             | \$3,995                                                                                                                         |
|  | 25.9A @120 AC<br>13.5A @230V                |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | \$6,995                                                                                                                         |
|  | 17.3A @120 AC<br>9.0A @230V                 |                                   |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             | \$5,795                                                                                                                         |
|  | 25.2A @120 AC<br>13.2A @230V                |                                   |                                                                                                                      | 140-265V / 70-135V<br>(45-66 Hz) |                                                                                                                                                                                                                                                                                                                             | W: 483 mm (19"), H: 88 mm<br>(2U), Overall D: 470 mm (18.5")<br>including handles and rear<br>support / 13 kg (29 lbs.)         |
|  | 23.9A @120 AC<br>12.5A @230V                | \$8,395                           |                                                                                                                      |                                  |                                                                                                                                                                                                                                                                                                                             |                                                                                                                                 |
|  | 1185W                                       | 90 to 132 VAC                     | 3.5 x19 x14.81 (2RU); 47.3 lbs.                                                                                      | 2                                | N/A                                                                                                                                                                                                                                                                                                                         | \$1,649.99                                                                                                                      |
|  | 3.25A @ 120VAC                              | 80 to 132 VAC or 160 to<br>264VAC | 3.5 x19 x 10.5 (2RU); 6.7 lbs.                                                                                       |                                  | Program-specific EQ presets that make<br>common sound-reinforcement EQ<br>treatments easy to perform, as well as<br>delays, crossover and stereo/mono op-<br>eration with lockable security settings                                                                                                                        | \$699.99                                                                                                                        |
|  | 12.1A @ 115 AC                              | 95 to 265 VAC                     | 2-rack space, 29.8 Lbs                                                                                               | 2                                | Delay, cross-over filters, Equalizer fil-<br>ters, Graphic equalizer, Cable compen-<br>sation network, Limiter                                                                                                                                                                                                              | \$8,968 / \$10,028 w/DSP                                                                                                        |
|  | 11.5A @120V                                 | 110 to 130V AC                    | 21 lbs. net                                                                                                          | 2                                | Network compatability                                                                                                                                                                                                                                                                                                       | \$1,749                                                                                                                         |
|  | 7.9A @120V                                  | 120v and 240v models              | 19" x 3 7/8" x 17 15/16" 27.6 lbs.                                                                                   | 2                                | N/A                                                                                                                                                                                                                                                                                                                         | PC9501 \$1,849; PC6501 \$1,499                                                                                                  |
|  | 15A,13.3A and 12.5A,<br>respectively @ 120V | Separate 120v and<br>240V models  | 19" x 3 7/8" x 18 1/8"<br>35.3lbs                                                                                    |                                  | The TXn provides separate input and<br>output processing. The onboard DSP<br>parameters and functions can be ac-<br>cessed directly through the LCD and<br>button interface provided on the front<br>panel of the amplifier, or via Yamaha\'s<br>amplifier control software running on a<br>computer connected via Ethernet | TX6n \$5,699, TX5n \$5,199, TX4n \$4,799                                                                                        |
|  | 12.5A @ 120V                                |                                   | 19" x 3 7/8" x 17 15/16," 26.5lbs                                                                                    |                                  | N/A                                                                                                                                                                                                                                                                                                                         | \$1,039                                                                                                                         |
|  | 25A @ 120v                                  |                                   | 4u 19"x18" depth 49lbs                                                                                               |                                  | 4                                                                                                                                                                                                                                                                                                                           | Flat no protection, or NEXO speaker<br>presets, plus Delay and Array EQ re-<br>mote controllable through ES monitor<br>software |